



72-7595

[Stk. No. 01J3056]

4-IN-1 ANEMOMETER, HYGROMETER, LUXMETER AND THERMOMETER



- Pocket Size Ergonomic 4-in-1 Meter
- Large Dual LCD
- Low-Friction Ball-Bearing Vane Wheel Improves Air Velocity Accuracy
- Simultaneously Displays Temperature and Air Velocity or Relative Humidity
- Type K Input for High Temperature Measurements to 2372°F (1300°C)
- Optional Type K Thermocouple Bead Probe (Type 72-2061)
- Selectable °C or °F For Temperature, Lux or Feet- Candle for Light Meter
- Data Hold, Recod (Min./Max.)

SPECIFICATIONS			
Measurement	Range	Resolution	Accuracy
Relative Humidity	10.0 to 95 RH%	0.10%	<70%RH: ±4%RH
			≥70%RH: ±(4% of rdg + 1.2%RH)
Temperature/Thermistor	32 to 122°F (-0 to 50°C)	0.1°F/°C	±2.5°F (± 1.2°C)
Temperature/Thermocouple (Type K)	-148 to 2372°F (-100 to 1300°C)	0.1°F (0.1°C)	± 1% + 2°F ± (1% + 1°C)
MPH (Miles Per Hour)	0.9 to 67.0 MPH	0.1MPH	≤20ms: ±3% F.S
			>20m/s: ±4% F.S
km/hr (Kilometers Per Hour)	1.4 to 108.0 km/h	0.1km/h	≤20ms: ±3% F.S
			>20m/s: ±4% F.S
Knots (Nautical Miles Per Hour)	0.8 to 58.3 knots	0.1knots	≤20ms: ±3% F.S
			>20m/s: ±4% F.S
m/sec (Meters Per Second)	0.40 to 30.0 m/s	0.01 ms	≤20ms: ±3% F.S
			>20m/s: ±4% F.S
ft/min (Feet Per minute)	80 to 5910 ft/min	1ft/min	≤20ms: ±3% F.S
			>20m/s: ±4% F.S

To browse, select, and order, visit www.spctechology.com