



DSP-4300 Digital CableAnalyzer™

The DSP-4300 Digital CableAnalyzer™ offers total Cat 6 solution:

- Exceeds specification requirements for Cat 5, Cat 5e and Cat 6 with Level III Accuracy, independently verified by both UL and ETL SEMKO
- Delivers more reliable PASS results with the new revolutionary Permanent Link
 Adapter – included with the DSP-4300
- Includes Cat 6 Channel Adapter and a Channel/Traffic Adapter so you're ready to test Cat 6 channel limits with DSP accuracy
- Automatically diagnoses cabling faults and shows exact locations in feet or meters
- Expanded 16 MB internal memory saves up to a full day's worth of testing (300 tests) if you forget your multimedia card, or fill up the card
- Download TIA-606A compliant Cable IDs to the DSP-4300 in the office to save time in the field and ensure accurate data
- Includes removable memory card and LinkWare™ Cable Test Management Software
- Optional Spool Test and Patch Cord Test Adapters verify cable and patch cord performance to the TIA/ISO Standards

And you have the assurance of performance, reliability and standards compliance backed and verified by both UL and ETL SEMKO.



The revolutionary Permanent Link Test Solution – included!

Our new DSP-LIA101S Permanent Link

Adapter delivers more passes. Eliminates costly false fail results due to worn twisted pair test leads. They develop internal wear and tear you can't see and before you know it – your link test fails. Falsely. That means wasted time in trouble-shooting. And blown re-testing costs. The new "non-twisted pair" design in our Permanent Link Adapter solves all that.

PM06 Personality Module certifies link and component compliance

The new DSP-4300 Pernament Link Adapter can be terminated with a choice of several personality modules to offer maximum flexibility and optimum test results. The DSP-4300 includes the standard PM06 Cat 6 Personality Module. The PM06 is the cabling industry's first centered, shielded test plug designed to certify link as well as connecting hardware compliance to the TIA/EIA-568-B.2-1 Cat 6 standard. The PM06 tests UTP, FTP and ScTP links and is the recommended solution for Cat 6, Cat 5e, Cat 5 and Cat 3 systems. No other solution allows you to see the true performance of the cabling system to achieve an "open" cabling system.

Channel Testing and Channel Traffic Monitoring

The DSP-4300 has you covered for Channel testing. Plug the Channel Adapter onto the DSP-4300 and you can test with confidence.







DSP-4000 Series Selection Guide

	DSP-4300	DSP-4100	DSP-4000PL	DSP-4000
Standard DSP Package*	•	•	•	•
Cat 6/5E Permanent Link Adapters w/PM06	•	**	•	**
Cat 6/5E Channel Adapters	•	•	•	
Cat 6/5E Channel/Traffic Adapter	•			
On-Board Memory-store up to 300 results	•		(summary test only; no graphical reports)	
MMC Card & Card Reader	•	•		
DSP-4300 Enhancement Kits				
DSP-4300E1 DSP-4100 to DSP-4300		•		
DSP-4300E0 DSP-4000 to DSP-4300			•	•

^{*}Standard DSP-4000 Series Package refers to Main and Remote test units, Talk Sets (2), Instrument Straps (2), DSP Calibration Module, RS-232 Serial Cable, 8-pin modular to BNC adapter, Rechargeable NiMH battery packs (2), AC Adapter/Chargers (2), LinkWare Software, Users Information CD-ROM, Getting Started Guide, Quick Reference Card, warranty registration card, and rugged soft case.

Ordering Information

Model	Items Included
DSP-4300	DSP-4300 Digital CableAnalyzer™
DSP-4000PL	DSP-4000PL Digital CableAnalyzer™
DSP-4000	DSP-4000 Digital CableAnalyzer™
LinkWare	LinkWare™ Software Free download from Fluke Networks' web site at www.flukenetworks.com/linkware

DSP-4000 Series Upgrades, Options and Accessories:

DSP-4300E1 Enhancement Kit: DSP-4100 to DSP-4300		
D3F-4300E1	Includes expanded on-board memory (16 MB), software upgrade, LinkWare software,	
	User Information CD and a Certified Calibration	
DSP-4300E0	Enhancement Kit: DSP-4000 to DSP-4300	
	Includes 16 MB Multimedia card, PC card reader, expanded on-board memory (16 MB),	
	software upgrade, LinkWare software, User Information CD and a Certified Calibration	
DSP-LIA101S	Permanent Link Adapter Set with Cat 6 Personality Modules	
	Includes two interface adapters that plug into the high performance connector of the DSP-4000 Series and a set of the PM06 Cat 6 centered Personality Modules	
	(Cat 6 8-pin modular plugs) to test Cat 6, Cat 5e, Cat 5 and Cat 3 links.	
DSP-LIA100S	Permanent Link Adapter Set	
	Includes two interface adapters that plug into the high performance connector of	
	the DSP-4000 Series. Does not include any Personality Modules.	
DSP-LIA101	Permanent Link Adapter (1)	
	Includes one replacement adapter that plugs into the high performance connector of the DSP-4000 Series. Does not include any Personality Modules.	
DSP-PCI-6S	DSP Patch Cord Test Adapter Set	
DSP-SPOOL	·	
	DSP Spool Test Adapter (1)	
DSP-LIA012S	Cat 6/5e Channel Adapter Set	
DSP-LIA013	Cat 6/5e Channel/Traffic Adapter (1)	
DSP-PM06	Cat 6 Centered Personality Module PM06 is the first centered, shielded plug to test Cat 6 compliance and	
New	interoperability. This global test solution supports all UTP, FTP and ScTP cabling	
PM06	systems, (Cat 3, Cat, 5, Cat 5e and Cat 6). Approved by major connectivity	
	manufacturers, for complete list go to www.flukenetworks.com/pmmatrix	
DSP-PMxx	Personality Modules for IDC & Legacy Systems	
	A wide selection of personality modules are available for IDC-type connectors as	
	well as legacy systems. For complete listing, go to www.flukenetworks.com/ legacypms	
DSP-FTA-420S	Multimode Fiber Test Adapter	
201 1111 1200	Uses LED light sources at 850 nm and 1300 nm	
DSP-FTA430S	Singlemode Fiber Test Adapter	
	Uses laser light sources at 1310 nm and 1550 nm wavelengths	
DSP-FTA440S	Gigabit Multimode Fiber Test Adapter	
	Uses a VCSEL source at 850 nm and laser source at 1310 nm	

With Remote Connector Compensation™ (RC²) you'll get the most accurate measurement results, giving you the true view of the cabling system's performance. Adding the Channel/Traffic Adapter extends your diagnostics and troubleshooting capabilities all in one tester.

Expanded on-board memory stores full day's results

Left your memory card at the office? Don't worry, the DSP-4300 has 16 MB of built-in internal memory, so you can test and save up to 300 full graphical test results to 350 MHz. Insert a 32 MB memory card and extend this to 600 results. Using the removable multimedia card allows you to keep the DSP on site. Take the memory card back to the office or mail the card to your customer.

Accurate cable ID download saves time

No more clumsy and time-consuming textentry to enter cable IDs into the DSP. Just download the cable IDs from any application that can generate a text file: for example, a labeling software, a database manager, a spreadsheet, LinkWare™

Software, or a third-party infrastructure management package. Downloading the cable IDs in advance saves time in the field by eliminating the need to manually enter cable IDs into the tester. It also saves time in the office by ensuring that test result IDs match exactly the cable IDs in the company's infrastructure management or labeling software.

Upgrade your DSP-4000 Series Digital CableAnalyzer

See ordering information for upgrade options for your DSP-4000 or DSP-4100.

N E T W O R K S U P E R V I S I O N

Fluke Networks

P.O. Box 777, Everett, WA USA 98206-0777

Fluke Networks operates in more than 50 countries worldwide. To find your local office contact details, go to www.flukenetworks.com/contact.

©2003 Fluke Corporation. All rights reserved. Printed in U.S.A. 10/2003 1626542 A-ENG-N Rev D

^{**}Cat 5e Basic Link Adapters